

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

febi 32936 Engine Oil 5W - 40
Article number: 32936, 32937, 32938, 32939, 32940

1.2 Relevant identified uses of the substance or mixture and uses advised against**1.2.1 Relevant uses**

Engine oil

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
 Wilhelmstr. 47
 58256 Ennepetal / GERMANY
 Phone +49 2333 911-0
 Fax +49 2333 911-444
 Homepage www.febi.com
 E-mail info@febi.com

Address enquiries to

Technical information info@febi.com

Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Eye Irrit. 2: H319 Causes serious eye irritation.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms**Signal word**

WARNING

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P280 Wear eye protection / face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice / attention.

2.3 Other hazards**Human health dangers**

Frequent persistent contact with the skin can cause skin irritation.
 If swallowed or in the event of vomiting, risk of product entering the lungs.

Environmental hazards

Does not contain any PBT or vPvB substances.

Other hazards

none

SECTION 3: Composition / Information on ingredients**Product-type:**

The product is a mixture.

Range [%]	Substance
45 - < 60	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 5	Polyolefine polyamine succinimid, polyol CAS: 147880-09-9, EINECS/ELINCS: Polymer GHS/CLP: Aquatic Chronic 4: H413
1 - < 5	Phenol, 2,2'-polythiobis[4-C8-30-alkyl derivs., calcium salts, overbased CAS: 90480-91-4, EINECS/ELINCS: 291-829-9, Reg-No.: 01-2119524004-56 GHS/CLP: Aquatic Chronic 4: H413
1 - < 2,5	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts CAS: 68649-42-3, EINECS/ELINCS: 272-028-3, Reg-No.: 01-2119493635-27-XXXX GHS/CLP: Aquatic Chronic 2: H411 - Eye Dam. 1: H318
< 0,25	Branched alkylphenol and calcium branched alkylphenol CAS: 74499-35-7 & 132752-19-3 GHS/CLP: Repr. 1B: H360 - Skin Irrit. 2: H315 - Eye Irrit. 2: H319 - Aquatic Chronic 1: H410, M = 1

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Take off contaminated clothing and wash before reuse.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

In case of contact with skin wash off immediately with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Consult a doctor immediately.
Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures**5.1 Extinguishing media****Suitable extinguishing media**

foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not be used

Full water jet

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.
Risk of formation of toxic pyrolysis products.
Phosphorus oxides (POx).
Sulphur oxides (SOx).
Nitrogen oxides (NOx).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Do not smoke.
Fire class (DIN EN 2): B
Do not eat, drink or smoke when using this product.
Use barrier skin cream.
Wash hands before breaks and after work.
Cloths contaminated with product should not be kept in trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Keep container tightly closed.
Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection**8.1 Control parameters****Ingredients with occupational exposure limits to be monitored (GB)**

not applicable

DNEL

Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
Industrial, inhalative, Long-term - local effects: 5.6 mg/m ³ 5.6 mg/m ³ .
Industrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day 5.6 mg/m ³ .
Industrial, inhalative, Long-term - systemic effects: 2.7 mg/m ³ .
general population, oral, Long-term - systemic effects: 0.74 mg/kg bw/day 5.6 mg/m ³ .

PNEC

Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
oral (food), 9,33 mg/kg.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances. General exposure limit for oil mist should be noted.
Eye protection	If there is a risk of splashing: safety glasses
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,11 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	Breathing apparatus in the event of aerosol or mist formation. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	yellow-brown
Odor	characteristic
Odour threshold	not applicable
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	No information available.
Flash point [°C]	> 200 (ISO 2592)
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	< 0,01 (20°C)
Density [g/ml]	0,858 (DIN 51757) (15 °C / 59,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Partition coefficient [n-octanol/water]	No information available.
Viscosity	> 20,5 mm²/s (40° C) ~ 13,5 - 15 mm²/s (100°C) (DIN 51562/T1)
Relative vapour density determined in air	No information available.
Evaporation speed	No information available.
Melting point [°C]	~ -36(ISO 3016)
Autoignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occur:
Hydrogen sulfide (H₂S).

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Product
oral, Based on the available information, the classification criteria are not fulfilled.:
inhalative, Based on the available information, the classification criteria are not fulfilled.:
dermal, Based on the available information, the classification criteria are not fulfilled.:
Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, dermal, Rabbit: ≥ 2000 mg/kg (OECD 402).
LD50, oral, Rat: ≥ 5000 mg/kg (OECD 401).
LC50, inhalative, Rat: $\geq 5,53$ mg/l (OECD 403).

Serious eye damage/irritation	Toxicological data of complete product are not available. Irritant Calculation method
Skin corrosion/irritation	Based on the available information, the classification criteria are not fulfilled.
Respiratory or skin sensitisation	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	No classification due to substance-specific concentration limits. SCL (CAS 74499-35-7&132752-19-3): $\geq 0,3\%$ H360
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	Toxicological data of complete product are not available. The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

SECTION 12: Ecological information**12.1 Toxicity**

Product
Based on the available information, the classification criteria are not fulfilled.:
Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
EL50, (24h), Daphnia magna: >10000 mg/l (OECD).
LL50, (96h), Pimephales promelas: >100 mg/l (OECD).
NOEL, (72h), Pseudokirchneriella subcapitata: >100 mg/l (OECD).
NOEL, (21d), Daphnia magna: 10 mg/l (OECD).

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	Can be separated out mechanically in purification plants.
Biological degradability	The product is only slightly biodegradable. Slightly eliminable from water.

Ferdinand Bilstein GmbH + Co. KG

Date printed 17.10.2017, Revision 17.10.2017

Version 07. Supersedes version: 06

Page 7 / 9

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available.
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!
Coordinate disposal with the disposal contractor/authorities if necessary.
Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110*

SECTION 14: Transport information**14.1 UN number**

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

Ferdinand Bilstein GmbH + Co. KG

Date printed 17.10.2017, Revision 17.10.2017

Version 07. Supersedes version: 06

Page 8 / 9

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	not applicable
--	----------------

Inland navigation (ADN)	not applicable
-------------------------	----------------

Marine transport in accordance with IMDG	not applicable
--	----------------

Air transport in accordance with IATA	not applicable
---------------------------------------	----------------

14.4 Packing group

Transport by land according to ADR/RID	not applicable
--	----------------

Inland navigation (ADN)	not applicable
-------------------------	----------------

Marine transport in accordance with IMDG	not applicable
--	----------------

Air transport in accordance with IATA	not applicable
---------------------------------------	----------------

14.5 Environmental hazards

Transport by land according to ADR/RID	no
--	----

Inland navigation (ADN)	no
-------------------------	----

Marine transport in accordance with IMDG	no
--	----

Air transport in accordance with IATA	no
---------------------------------------	----

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EEC-REGULATIONS	1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014
------------------------	---

TRANSPORT-REGULATIONS	DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2017).
------------------------------	---

NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
-----------------------------------	--

- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
--	--

- VOC (2010/75/CE)	0 %
--------------------	-----

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information**16.1 Hazard statements
(SECTION 03)**

H410 Very toxic to aquatic life with long lasting effects.
 H319 Causes serious eye irritation.
 H315 Causes skin irritation.
 H360 May damage fertility or the unborn child.
 H318 Causes serious eye damage.
 H411 Toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.
 H304 May be fatal if swallowed and enters airways.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV®/TWA = Threshold limit value – time-weighted average
 TLV®STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information**Classification procedure**

Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)

Modified position

SECTION 3 been added: Phenol, 2,2'-polythiobis[4-C8-30-alkyl derivs., calcium salts, overbased

SECTION 3 deleted: Phenol, 2,2'-polythiobis[4-C8-30-alkyl derivs., calcium salts, overbased